

JETPOWER™

BATTERIES

An ISO 9001 : 2008 Certified Co.




24 Months Replacement Warranty

LEAD ALLOY



Specially mixed selenium lead alloy used for plate grid casting, it reduces water topping up frequencies (low maintenance)

TUBULAR GAUNTLETS



Tubular positive plates consisting of alloy Grids & properly balanced active material Encased in chloring free polyester gauntlets of high bursting strength & high performance (HP)

P E SEPARATORS



Low internal resistance polyethylene Envelope type separators with glass mat to internal life of batteries by preventing internal short in between positive and negative electrodes.

L SHAPED TERMINALS



"L" shaped terminals welded for easy installation with SS fastners to avoid sulphation / corrosion.

DEEP CYCLE BATTERIES

High Performance ✓

जिसपर भारतीय करें भरोसा

A QUALITY PRODUCT OF :



INVERTER | SOLAR BATTERY | TUBULAR BATTERY



JETPOWER™

BATTERIES

An ISO 9001 : 2008 Certified Co.

FAST FACTS

- ☞ Heat Sealed Tubular stationary batteries for UPS & Inverters.
- ☞ Separators are made of high quality micro porous material .
- ☞ Positive Tubular plate with low antimony alloy to reduce frequency of topping up intervals.
- ☞ Negative plates are of pasted grid type with lead calcium alloy.
- ☞ Micro porus Aqua-trap Ceramic Vent Plugs for individual cells –prevent acid mist coming out from the cells making it convenient for living room.

JETPOWER BATTERIES TECHNICAL SPECIFICATION SHEET

Type 12 V Range	Nominal Capacity at 10 Hrs. Rate (12 Volt)	Normal (V) Voltage	Battery Weight Filled WT (KG)	Overall Dimensions In (MM) L (MM) W (MM) H (MM) Approximately			Approx. Acid Qty.	Charging Current
JTS 20-12	20	12	10	180	120	201	2.2	2.00
JTS 40-12	40	12	13.5	195	127	225	3.5	4.00
JTS 75-12	75	12	24.5	260	173	235	6.2	7.5
JTS 100-12	100	12	30.00	413	175	249	7.9	10.00
JTS 120-12	120	12	39.00	413	178	349	9.00	12.00
JTS 135-12	135	12	48.00	513	215	250	12.00	13.5
JTS 150-12	150	12	55.00	518	275	265	13.5	15.00
JTS 180-12	180	12	62.00	518	275	265	14.8	18.00
JTS 200-12	200	12	68.00	522	280	270	15.9	20.00

PRODUCT CHARACTERISTICS

PLATE DESIGN :

JETPOWER plates are casted on the automatic grid casting machines ensuring a proper uniformity and better quality. The plate contains approximately 3.0% antimony providing higher tolerance of cycling at elevated temperatures. It eliminates problems related levels of antimony – like high gassing and internal power loss on charge. Extra heavy duty plates manufactured as per exclusive JETPOWER design. Ensuring durability, resistance to corrosion & inbuilt margins for high ambient temperatures & deep cyclic use.

BEYOND AMPERES & WATTS :

With the collaboration of best brains and technicians in the industry, JETPOWER batteries are constantly breaking new grounds in battery technology. It has adopted Global standards to bring its customers international quality batteries at Indian prices. JET POWER offers a comprehensive range of products that are finished to perfection. Our wide range of products includes Inverter, Solar and Tubular batteries with unmatched features with least pollution and low maintenance batteries.

Note : Technical Specification are subject to change without prior notice A QUALITY PRODUCT OF :

JETPOWER™ DEALER

An ISO 9001:2008 Co.

JTS
POWER Pvt. Ltd.


Go Green

F-110, First Floor, DDA Building No.5, Near Satyam Cineplex,
 Distt. Centre Janak Puri, New Delhi-110058, India
 Tel. No.: +91-11-25537002, 65420202 Fax : +91-11-41034949
 E-mail : jtspower@gmail.com, sales@jetpower.in

INVERTER | SOLAR BATTERY | TUBULAR BATTERY